### **Fuelling products**

# Coupling

## 2 1/2-inch self sealing industrial couplings

2 1/2-inchnself sealing industiral couplings



#### **GENERAL INFORMATION**

Meggitt self sealing couplings are designed for use wherever it is necessary to connect and disconnect hoses and pipelines under pressure, quickly and without spillage. They are designed primarily for use in the petroleum and chemical industries where reliability and safety are of prime concern.

### **Key Features**

- Low cost
- Fail safe tank units
- Unrivalled quality for trouble free operation and long life
- Negligible spillage
- Environmentally friendly
- Easy single action coupling and valve opening
- Material: gunmetal
- Nitrile or fluorocarbon seals
- Seven selectivity options



### **Fuelling products**

# Couplings

## 2 1/2-inch self sealing industrial couplings

### **Specification**

#### **OPERATION**

Operation is single action, using a straightforward turning motion to connect the couplings and open a flow path.

An initial push and turn action on the hose unit causes engagement with the tank unit, thus locking and sealing the two units together. Further rotation causes the internal valves to open, thereby allowing flow with minimum pressure drop.

The connection and valve mechanism is interlocked such that the valve can only be opened by fully engaging and sealing the hose unit on its matching tank unit.

On disconnection, the valves fully close before the couplings separate and spillage is therefore negligible.

1

#### 1 - HOSE UNIT

Materials Weight Max. Working Pressure Max. Coupling Pressure Test Pressure

#### CCMY 6253N\*

Gunmetal, St/Steel 5.7 kg (12.6 lb) 175 psi (12bar) 60 psi (4 bar) 265 psi (18 bar)

